

May 2025

Class 1 uPVC Duct



Available in **Red** & **Black**

uPVC power cable duct is a single wall duct manufactured under ISO 9001:2015, compliant with ENATS 12-24 for Class 1 performance. uPVC power cable duct is produced with inbuilt interference fit sockets tested to IP4X in accordance with BS EN 60529.



Material	Unplasticized Polyvinyl Chloride (uPVC)
Marking	ELECTRIC CABLE DUCT C1 NAYLOR SIZE dd-mm-yy HH:MM LINE
Quality System & Inspection	All quality systems and inspection procedures comply with BS EN ISO 9001: 2015 (Certificate No: FM 01420)
Standards & Certification	uPVC duct is manufactured in accordance with ENA TS 12-24 and BS EN 61386-24. Complies with manufacturing and test requirements of ENA TS 12-24 (Certificate No A3122)
Packaging	Supplied in 3 or 6 metre lengths as standard in timber framed packs (quantity of product per packaged unit is dependent upon the external diameter of the product)
Storage	For long term storage keep away from direct sunlight to avoid product degradation, over 12 months exposure to direct sunlight should be avoided

100/110mm (ID/OD) PVC CLASS 1				
OD	Length	Product	Code	Code
110mm	6m	ELEC CLASS 1 PVC DUCT PIPE S/S	30113	30112
110mm	3m	ELEC CLASS 1 PVC DUCT PIPE S/S	30110	30111
110mm	-	PVC Coupler D/S	36109	36100
110mm	-	11.25 deg 1.2m Rad Class 1 PVC Bend S/S	36121	36121
110mm	-	22.5 deg 1.2m Rad Class 1 PVC Bend S/S	36102	36112
110mm	-	45 deg 1.2m Rad Class 1 PVC Bend S/S	36105	36115
110mm	-	90 deg 1.2m Rad Class 1 PVC Bend S/S	36106	36116

150/160mm (ID/OD) PVC CLASS 1				
OD	Length	Product	Code	Code
160mm	6m	ELEC CLASS 1 PVC DUCT PIPE S/S	30161	30163
160mm	3m	ELEC CLASS 1 PVC DUCT PIPE S/S	30160	30162
160mm	-	PVC Coupler D/S	36701	36700
160mm	-	11.25 deg 1.2m Rad Class 1 PVC Bend S/S	36161	36261
160mm	-	22.5 deg 1.2m Rad Class 1 PVC Bend S/S	36162	36262
160mm	-	45 deg 1.2m Rad Class 1 PVC Bend S/S	36163	36263
160mm	-	90 deg 1.2m Rad Class 1 PVC Bend S/S	30164	36268