## Sheet Product Data

## May 2025 **Class 1 uPVC Duct**

Available in Red & Black

uPVC power cable duct is a single wall duct manufactured under ISO 9001:2015, compliant with ENATS 12-24 for Class 1 performace. uPVC power cable duct is produced with inbuilt interference fit sockets tested to IP4X in accordance with BS EN 60529.



Material	Unplasticized Polyvinyl Chloride (uPVC)
Marking	ELECTRIC CABLE DUCT CI NAYLOR SIZE dd-mm-yy HH:MM LINE
Quality System & Inspection	All quality systems and inspection procedures comply with BS EN ISO 9001: 2015 (Certificate No: FM 01420)
Standards & Certification	uPVC duct is manufactured in accordance with ENA TS 12-24 and BS EN 61386-24. Complies with manufacturing and test requirements of ENA TS 12-24 (Certificate No A3122)
Packaging	Supplied in 3 or 6 metre lengths as standard in timber framed packs (quantity of product per packaged unit is dependent upon the external diameter of the product)
Storage	For long term storage keep away from direct sunlight to avoid product degradation, over 12 months exposure to direct sunlight should be avoided

100/110mm (ID/OD) PVC RED CLASS 1				
OD	Length	Product	Code	
110mm	6m	RED ELEC CLASS 1 PVC DUCT PIPE S/S	30081	
110mm	3m	RED ELEC CLASS 1 PVC DUCT PIPE S/S	30080	
110mm	-	RED PVC Coupler D/S	36109	
110mm	-	11.25 deg 1.2m Rad RED Class 1 PVC Bend S/S	36121	
110mm	-	22.5 deg 1.2m Rad RED Class 1 PVC Bend S/S	36102	
110mm	-	45 deg 1.2m Rad RED Class 1 PVC Bend S/S	36105	
110mm	-	90 deg 1.2m Rad RED Class 1 PVC Bend S/S	36106	

All descriptions and illustrations in this publication are intended for guidance only and shall not constitute a 'sale by description'. All dimensions given are nominal and NAYLOR may modify and change the information, products and specifications from time to time for a variety of reasons, without prior notice. The information in this publication is provided 'as is' and will not be issued automatically.

This information is not intended to have any legal effect, whether by way of advice, representation or warranty )express or implied). We accept no liability whatsoever (to the extent permitted by law) if you place any reliance on this publication, you do so at your own risk. All rights reserved. Copyright in this publication belongs to NAYLOR and all such copyright may not be used, sold, copied or reproduced in whole or part in any manner in any media to any person with prior consent.

Technical Support Our dedication technical team is available for guidance and assistance.

For further information, please contact our Support Team help@naylor.co.uk

naylor-power.co.uk

# naylor

100/110mm (ID/OD) PVC BLACK CLASS 1				
OD	Length	Product	Code	
110mm	6m	BLACK ELEC CLASS 1 PVC DUCT PIPE S/S	30112	
110mm	3m	BLACK ELEC CLASS 1 PVC DUCT PIPE S/S	30111	
110mm	-	BLACK PVC Coupler D/S	36100	
110mm	-	11.25 deg 1.2m Rad BLACK Class 1 PVC Bend S/S	36121	
110mm	-	22.5 deg 1.2m Rad BLACK Class 1 PVC Bend S/S	36112	
110mm	-	45 deg 1.2m Rad BLACK Class 1 PVC Bend S/S	36115	
110mm	-	90 deg 1.2m Rad BLACK Class 1 PVC Bend S/S	36116	

150/160mm (ID/OD) PVC RED CLASS 1				
OD	Length	Product	Code	
160mm	6m	RED ELEC CLASS 1 PVC DUCT PIPE S/S	30162	
160mm	3m	RED ELEC CLASS 1 PVC DUCT PIPE S/S	30160	
160mm	-	RED PVC Coupler D/S	36701	
160mm	-	11.25 deg 1.2m Rad RED Class 1 PVC Bend S/S	36161	
160mm	-	22.5 deg 1.2m Rad RED Class 1 PVC Bend S/S	36162	
160mm	-	45 deg 1.2m Rad RED Class 1 PVC Bend S/S	36163	
160mm	-	90 deg 1.2m Rad RED Class 1 PVC Bend S/S	36164	

150/160mm (ID/OD) PVC BLACK CLASS 1				
OD	Length	Product	Code	
160mm	6m	BLACK ELEC CLASS 1 PVC DUCT PIPE S/S	30163	
160mm	3m	BLACK ELEC CLASS 1 PVC DUCT PIPE S/S	30160	
160mm	-	BLACK PVC Coupler D/S	36700	
160mm	-	11.25 deg 1.2m Rad BLACK Class 1 PVC Bend S/S	36261	
160mm	-	22.5 deg 1.2m Rad BLACK Class 1 PVC Bend S/S	36262	
160mm	-	45 deg 1.2m Rad BLACK Class 1 PVC Bend S/S	36263	
160mm	-	90 deg 1.2m Rad BLACK Class 1 PVC Bend S/S	36168	

### Power ø

All descriptions and illustrations in this publication are intended for guidance only and shall not constitute a 'sale by description'. All dimensions given are nominal and NAYLOR may modify and change the information, products and specifications from time to time for a variety of reasons, without prior notice. The information in this publication is provided 'as is' and will not be issued automatically.

This information is not intended to have any legal effect, whether by way of advice, representation or warranty )express or implied). We accept no liability whatsoever (to the extent permitted by law) if you place any reliance on this publication, you do so at your own risk. All rights reserved. Copyright in this publication belongs to NAYLOR and all such copyright may not be used, sold, copied or reproduced in whole or part in any manner in any media to any person with prior consent.

Technical Support Our dedication technical team is available for guidance and assistance.

For further information, please contact our Support Team help@naylor.co.uk

naylor-power.co.uk